



MANUFACTURING STANDARDS:

Structural Steelwork:
BS EN 10210-1:1994, BS EN 10210-2:1997

General Steelwork:
BS 1449:1991, BS 1387:1985, BS EN 10025:1993

Welding Procedures:
Comply with BS 5135:1984

Hot Dipped Galvanized:
BS EN 729:1971, BS EN ISO 1461:1999

Fasteners:
Grade 8.8 BS 3692:2001, BS 4190:2001,
DIN 931, DIN 934

Design Wind Loadings:
Based on CP3 Chapter V Pt 2 (1972) &
BS 6399 Pt 2 (1997)

Paint Finishes:
BS 4800 & RAL colour range

PRODCUCT CODE	HEIGHT MTR A	POLE DIA B	PIVOT HEIGHT C	PIVOT SECTION D	GUSSETT THICKNESS	BASE PLATE THICKNESS	DOOR APPERTURE DIMENSIONS	REAR TILT CLEARANCE E	WEIGHT KGS
TDTP4	4	127	1500	150 sq	6	12	400 (h) x 120 (w)	1500	150
TDTP5	5	127	1500	150 sq	6	12	400(h) x 120 (w)	1500	162
TDTP6	6	127	1500	150 sq	6	12	400 (h) x 120 (w)	1500	179
TDTP7	7	127	1500	150 sq	6	12	400 (h) x 120 (w)	1500	198
TDTP8	8	168	2000	200 sq	8	15	450 (h) x 180 (w)	2000	245
TDTP9	9	168	2500	200 sq	10	20	450 (h) x 180 (w)	2500	329
TDTP10	10	168	2500	200 sq	10	20	450 (h) x 180 (w)	2500	429
TDTP11	11	193	2500	200 sq	12	25	450 (h) x 180 (w)	2500	479
TDTP12	12	193	2500	200 sq	12	25	450 (h) x 180 (w)	2500	529

All dimensions in the above table are in mm unless otherwise stated.