



**MANUFACTURING STANDARDS:**

Structural Steelwork:  
BS EN 10210-1:1994, BS EN 10210-2:1997

General Steelwork:  
BS 1449:1991, BS 1387:1985, BS EN 10025:1993

Welding Procedures:  
Comply with BS 5135:1984

Hot Dipped Galvanized:  
BS EN 729:1971, BS EN ISO 1461:1999

Fastners:  
Grade 8.8 BS3692:2001, BS 4190:2001,  
DIN 931, DIN 934

Design Wind Loadings:  
Based on CP3 Chapter V Pt 2 (1972) &  
BS 6399 Pt 2 (1997)

Paint Finishes:  
BS 4800 & RAL colour range

PRODCUT CODE	HEIGHT MTR	POLE DIA	PIVOT HEIGHT	PIVOT SECTION	GUSSETT THICKNESS	BASE PLATE THICKNESS	DOOR APPERTURE DIMENSIONS	REAR TILT CLEARANCE	WEIGHT KGS
	A	B	C	D				E	
TDTP4	4	127	1500	150 sq	6	12	400 (h) x 120 (w)	1500	150
TDTP4.5	4.5	127	1500	150 sq	6	12	400 (h) x 120 (w)	1500	156
TDTP5	5	127	1500	150 sq	6	12	400(h) x 120 (w)	1500	162
TDTP6	6	127	1500	150 sq	6	12	400 (h) x 120 (w)	1500	179
TDTP7	7	168	2000	200 sq	8	15	450 (h) x 180 (w)	2000	198
TDTP8	8	168	2000	200 sq	8	15	450 (h) x 180 (w)	2000	245
TDTP9	9	168	2500	200 sq	10	20	450 (h) x 180 (w)	2500	329
TDTP10	10	168	2500	200 sq	10	20	450 (h) x 180 (w)	2500	429
TDTP11	11	193	2500	200 sq	12	25	450 (h) x 180 (w)	2500	479
TDTP12	12	193	2500	200 sq	12	25	450 (h) x 180 (w)	2500	529